







# ACCOYA® HAS PROPERTIES THAT MATCH OR EXCEED THOSE OF THE BEST TROPICAL HARDWOODS AND TREATED WOODS.

**50 Year Warranty Rot and Insect Barrier** Paint and Stain Lasts 3-5 Times Longer





# WINDOWS AND DOORS

Swing freely because Accoya® swells very little.

Paint and stain lasts 3–5 times longer on Accoya® so your windows and doors will look great for many years.

Less maintenance required which increases the cost effectiveness of using Accoya.

Provide your customers with the transferable 50 year Accoya® warranty

# EXCEPTIONAL EXTERIOR PERFORMANCE

5 Year Weathering Test\*





Accoya Modified Wood Pristine after 5 years exposure. Western Red Cedar

\* Independent 3rd party testing by BM Trada



# SIDING AND EXTERIOR TRIM

- Ideal choice where aesthetics and less frequent maintenance are important to you
- Dimensional stability, durability and natural UV resistance of Accoya wood confirms a decreased overall life cycle cost





Requires complete refinishing after 5 years.

### DECKS AND DOCKS

In specifying decking you want...

Natural beauty, strength and allweather performance are important

A lasting wood with outstanding performance characteristics and dimensional stability is desirable

Also critical that the wood is non-toxic and therefore safe for people and pets

Accoya wood meets all these requirements and more.

# ACCOYA® WOOD PRODUCT DETAILS

## MATERIAL

4 sides clear of knots and defects

#### DIMENSIONS

Thickness 4/4, 6/4, 8/4, 10/4 and 12/4. True dimension ie) 4/4 is 1″ or 25mm

Lengths 8' to 16'

#### SHRINK AND SWELL

A fraction of the movement of other woods. Accoya<sup>®</sup> is .7% radial and 1.5% tangential

#### DURABILITY

A fraction of the movement of other woods. Accoya® is .7% radial and 1.5% tangential

#### FIRE RATING

**Class C** Accoya<sup>®</sup> can be after market treated with fire retardants to achieve a Class A rating

### FSC<sup>®</sup> CERTIFIED

# **50 YEAR WARRANTY**

This warranty is exclusive to the original owner of any structure on which the Accoya<sup>®</sup> wood is installed and the next owner of that structure.

- **50 years** when the Accoya® wood product is used above ground
- **25 years** when the Accoya<sup>®</sup> wood product is used at or below ground level

Access your copy of the Accoya® wood Warranty at www.ucfp.com

# GUIDELINES FOR USE

# GLUING

Accoya<sup>®</sup> wood can be glued using many commonly used wood adhesive systems. Particularly good results are obtained with polyurethane (PU), emulsion polymer isocyanate (EPI), epoxy and phenol resorcinol formaldehyde (PRF) adhesives.

# FASTENERS & OTHER HARDWARE

Corrosion-resistant, high quality 304 or 316 stainless steel or naval brass fasteners are recommended.

# COATINGS

Most high quality outdoor approved wood coating systems last three or more times longer.

#### MACHINABILITY

Accoya<sup>®</sup> machines more like a hardwood and requires no special tools for cross cutting, ripping, planning, routing or drilling.

#### DISPOSAL

Dispose like regular wood



Upper Canada Forest Products 1866 265 0624 | www.ucfp.com Torontosales\_toronto@ucfp.comEdmontonsales\_edmonton@ucfp.comCalgarysales\_calgary@ucfp.comKelownasales\_kelowna@ucfp.comVancouversales\_vancouver@ucfp.com

